



# TSBA2T045S(A)S-310A

## 10A/45V<sup>(1)</sup>, low VF Schottky barrier diode with trench MOS structure

### Mechanical Data

Chip Drawing	Item	Information	
	Die Size (A)	2590 μm	102 mil
	Top Metal Pad Size (B)	2481 μm	97mil
	Chip Size (C)	2489μm	98mil
	Wafer Thickness (D)	310 μm	11.4 mil
	Scribe Line Width (E)	80 μm	3.15 mil
	Wafer Size	6 inch	
	Top Side Metallization	TSBA2T045SS-310A	Al/Ag
	Back Side Metallization	Ti Ni Ag	
	Recommended Storage Environment	Stored in original container, in dry nitrogen, (6 months at an ambient temperature of 23°C±3°C)	

### Electrical Characteristics (T<sub>J</sub>=25°C, unless otherwise specified)<sup>(2)</sup>

Parameter	Description	Min.	Typ.	Max.	Unit	Test Condition
V <sub>BR</sub>	Reverse Breakdown Voltage	47	50	-	V	I <sub>R</sub> =100μA
V <sub>F</sub>	Instantaneous Forward Voltage	-	0.430	0.48	V	I <sub>F</sub> =10A <sup>(3)</sup>
I <sub>R</sub>	Reverse Leakage Current	-	40	70		V <sub>R</sub> =45V
T <sub>J</sub> , T <sub>STG</sub>	Operating and Storage Temperature	-40°C to 150°C Max				

#### Note:

(1) The preliminary wafer datasheet only for reference;

(2) This characteristics assumes the dies are assembled in R-6 packages. Actual performance may degrade when assembled. YJ does not guarantee device performance after assembly;

(3)